



Samsung Mono Laser MFPs SCX-4833FD/SCX-5737FW



Key Features:

- Print Speeds up to 31ppm/35ppm in A4
- First Print Out Time 6.5 seconds (from Ready Mode)
- Improved Print Quality with up to 1,200 x 1,200dpi
- Maximum Monthly Duty Cycle 50,000/80,000 sheets
- Quiet Operation at less than 52/53dBA (printing)
- Standard Cartridge Yield of 2,000/5,000 pages
- 250-sheet Input Capacity, 50-sheet Multi-Purpose tray
- Instant Wireless at the touch of a button with the Wi-Fi Protected Set up (WPS) button¹

The simple business workflow solution.

Recent trends have shown that businesses are looking at their print environment as a way of driving efficiency throughout their business. By replacing out-dated inefficient printers and copiers with energy efficient multifunction devices they can achieve productivity gains, improved device availability and significantly reduced costs and carbon footprint.

Introducing the Samsung SCX-4833FD/SCX-5737FW mono laser multifunction printers. These intelligently designed devices offer reliable and fast performance alongside ease of use for maximum usability across the organisation. Their high ECO credentials make them an ideal option for businesses that are looking to reduce their environmental impact as well as reduce costs, increase productivity, improve workflow and boost overall competitiveness.

¹ SCX-5737FW only ² SCX-4833FD only

Top 3 Reasons to Buy:

- 1 User-Friendly and Reliable:**
 - Handy 4.3" touch screen¹ for access to a wide array of features and settings on the SCX-5737FW
- 2 Value for Money:**
 - Easily switch to Toner Save Mode for economical printing
 - Lower cost per page and fewer toner replacements with extra high yield toner cartridges.
- 3 Productivity Boosting Performance:**
 - Save time with the built-in 50 sheet duplex¹ Automatic Document Feeder (ADF) and a Duplex feeder (DADF) on the SCX-5737FW
 - 600MHz dual-core processor², Gigabit network connectivity² and up to 768 MB memory² for fast output
 - Fast printout speeds of up to 35ppm¹.

Product Configurations

SCX-4833FD (front)

Control Panel

Output Tray

Multi-Purpose Tray

Standard Tray

Optional Tray

Paper Level Indicator

ADF Document Feeder

SCX-4833FD (back)

- Network Cable
- Hi-Speed USB 2.0 Port for Direct Connection
- 5v Output for Parallel Port Option
- Power Cord

SCX-5737FW

Output Tray

- DADF Duplex Document Feeder
- LCD Menu Screen

- Multi-Purpose Tray
- Paper Level Indicator

Product Datasheet

Samsung Mono Laser MFPs SCX-4833FD/SCX-5737FW

Product Specifications

	SCX-4833FD	SCX-5737FW
Print		
Speed (Mono)	Up to 31ppm in A4 (33ppm in Letter)	Up to 35ppm in A4 (37ppm in Letter)
First Print Out Time (Mono)	6.5 Seconds	
First Print Out Time	Up to 1,200 x 1,200dpi effective output	
Emulation	PCL5e/6, PS3, Epson/IBM Pro, PDF, TIFF	PCL5e/6, PS3, XPS, Epson/IBM Pro, PDF, TIFF
Duplex	Built-in	
Copy		
Speed	Up to 31ppm in A4 (33ppm in Letter)	Up to 35ppm in A4 (37ppm in Letter)
Resolution	Up to 1200 x 1200dpi effective output	
First Copy Out Time (Mono)	12 Seconds	10 Seconds
Zoom Rate	25~400% (platen), 25~100% (ADF)	
Multi Copy	1~99 pages	
Duplex Copy	Standard (1:1, 1:2)	
Copy Features	ID Copy, 2-up, 4-up, Poster Copy, Clone Copy, Collation Copy, Auto-fit	
Scan		
Scan Speed(B/W)	20ipm	24ipm
Scan Size Document	Platen: Width (~216mm, 8.5"), Length (~297mm, 11.69"). ADF: Width (142~216mm, 5.6" ~ 8.5"), Length (148 ~ 356mm, 5.8" ~ 14")	
Compatibility	TWAIN Standard, WIA Standard	
Method	Colour CIS	
Resolution (Optical)	1200 x 1200dpi	
Resolution (Enhanced)	Up to 4,800 x 4,800dpi	
Scan to	PC, Email, USB Memory	PC, Email, USB Memory, FTP, SMB, Internal Flash Drive
FAX		
Compatibility	ITU-T G3	
Modem Speed	33.6Kbps	
Resolution	Standard: 203 x 98dpi, Fine/Photo: 203 x 196dpi, Super Fine: 300 x 300dpi, Colour: Up to 200 x 200dpi	
Memory	5MB (Max. 445 Pages)	50MB (Max. 4,000 Pages)
Auto Dial	Speed dial: 200 Locations	
Fax Feature	On hook Dial, Auto Redial, Last Number Redial, Auto Reduction, Multi-Send, Delayed Send, Fax Forwarding (Email/Fax), Broadcasting up to 209 locations	
Paper Handling		
Input Capacity and Types	250-sheet Cassette, 50-sheet Multi Purpose Tray	
Output Capacity and Type	150-sheet Face Down, 1-sheet Face Up	
Media Size	76 x 127mm (3" x 5") ~ 216 x 356mm (8.5" x 14")	
Media Type	Plain, Thin, Thick, Thicker, Cotton, Coloured, Envelope, Transparency, Pre-Printed, Recycled, Labels, Bond, Card stock, Archive	
ADF Capacity	50-sheet	
ADF Document Size	Width: 142 ~ 216mm (5.6" ~ 8.5") / Length: 148 ~ 356mm (5.8" ~ 14.0")	
Envelope Capacity	5 sheets	
General		
Processor	Samsung 360Mhz	Samsung 600 MHz
LCD	2-line LCD	4.3" Colour Touch-Screen LCD
Memory/Storage	128MB (Max 384MB)	256MB (Max 768MB) / 4GB Internal Flash Drive
OS Compatibility	Microsoft Windows: 2000/XP (32/64 bit), Vista (32/64 bit), 2003 Server (32/64 bit), 2008 Server (32/64 bit), Windows 7 (32/64 bit), 2008 Server R2 (64 bit); Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit), Fedora 5 to 13 (32/64 bit), SuSE Linux 10.1 (32 bit), OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit), Mandriva 2007 to 2010 (32/64 bit), Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10, 10.04 (32/64 bit), SuSE Linux Enterprise Desktop 10, 11 (32/64 bit), Debian 4.0, 5.0 (32/64 bit).	
Interface	Hi-Speed USB 2.0, Ethernet 10/100 Base TX	Hi-Speed USB 2.0, Ethernet 10/100/1000 Base TX, IEEE 802.11 b/g/n Wireless Network
Noise Level	Less than 52dBA (Printing); Less than 54dBA (Copying); Less than 26dBA (Standby)	Less than 53dBA (Printing); Less than 54dBA (Copying); Less than 26dBA (Standby)
Duty Cycle, Monthly	Up to 50,000 pages	Up to 80,000 pages
Dimension (WxDxH)	424 x 382 x 407mm	469 x 438 x 447mm
Weight	14.37kg	16.55kg
Power Consumption	550W(Active)/50W(Ready)/8W(Sleep)	600W(Active)/65W(Ready)/10W(Sleep)

Consumables

Yield	Standard: Average Cartridge Yield 2,000 standard pages. High Yield: Average Cartridge Yield 5,000 standard pages. Ships with 2,000 pages Starter Toner Cartridge. Declared Cartridge Yield in accordance with ISO/IEC 19752.	Standard: Average Cartridge Yield 2,000 standard pages. High Yield: Average Cartridge Yield 5,000 standard pages. Extra High Yield: Average Cartridge Yield 10,000 standard pages. Ships with 5,000 pages Starter Toner Cartridge. Declared Cartridge Yield in accordance with ISO/IEC 19752.
Type	1-piece Cartridge	
Codes	MLT-D205S/ELS - 2,000 Pages, MLT-D205L/ELS - 5,000 Pages	MLT-D205S/ELS - 2,000 Pages, MLT-D205L/ELS - 5,000 Pages, MLT-D205E/ELS - 10,000 Pages
Options		
Options	-520-sheet Cassette Tray - ML-S3710A/SEE -Memory (256MB) - ML-PAR100/SEE -IEEE 1284B Parallel Connector - ML-PAR100/SEE	-520-sheet Cassette Tray - ML-S3050A/SEE -Memory (512MB) - ML-MEM170/SEE -IEEE 1284B Parallel Connector - ML-PAR100/SEE



For more information, please visit www.samsung.com/uk/printer